


# DESIGNER

SERIES



PLANAR  
HORIZONTAL

## 50 $\Delta$ t

(75/65/20°C)

K1



K2



Height mm	Length mm	Sections	Stelrad UIN	Heat output		Stelrad UIN	Heat output	
				Watts	Btu/hr		Watts	Btu/hr
<b>300</b>	500	15	140900	235	802	140904	465	1587
	1000	30	140901	469	1601	140905	929	3171
	1400	42	140902	657	2242	140906	1301	4440
	2000	60	140903	938	3201	140907	1858	6341
<b>400</b>	400	12	140908	250	853	140917	471	1608
	600	18	140909	376	1283	140918	706	2410
	800	24	140910	501	1710	140919	942	3215
	1000	30	140911	626	2137	140920	1177	4017
	1200	36	140912	751	2563	140921	1412	4819
	1400	42	140913	876	2990	140922	1648	5625
	1600	48	140914	1002	3420	140923	1883	6427
	1800	54	140915	1127	3846	140924	2119	7232
2000	60	140916	1252	4273	140925	2354	8034	
<b>500</b>	400	12	140926	310	1058	140935	564	1925
	600	18	140927	464	1584	140936	847	2891
	800	24	140928	619	2113	140937	1129	3853
	1000	30	140929	774	2642	140938	1411	4816
	1200	36	140930	929	3171	140939	1693	5778
	1400	42	140931	1084	3700	140940	1975	6741
	1600	48	140932	1238	4225	140941	2258	7707
	1800	54	140933	1393	4754	140942	2540	8669
2000	60	140934	1548	5283	140943	2822	9631	
<b>600</b>	400	12	140944	364	1242	140953	654	2232
	600	18	140945	547	1867	140954	980	3345
	800	24	140946	729	2488	140955	1307	4461
	1000	30	140947	911	3109	140956	1634	5577
	1200	36	140948	1093	3730	140957	1961	6693
	1400	42	140949	1275	4352	140958	2288	7809
	1600	48	140950	1458	4976	140959	2614	8922
	1800	54	140951	1640	5597	140960	2941	10038
2000	60	140952	1822	6218	140961	3268	11154	
<b>700</b>	400	12	140974	415	1417	140983	739	2522
	600	18	140975	623	2125	140984	1109	3783
	800	30	140976	830	2833	140985	1478	5044
	1000	36	140977	1038	3542	140986	1848	6305
	1200	42	140978	1246	4250	140987	2218	7566
	1400	48	140979	1453	4958	140988	2587	8828
	1600	54	140980	1661	5667	140989	2957	10089
	1800	60	140981	1868	6375	140990	3326	11350
2000	66	140982	2076	7083	140991	3696	12611	


$\Delta$ t50 is the UK's industry standard for heating outputs, which has an operating temperature of 75/65/20°C. If you have a low temperature heat source you may wish to consider  $\Delta$ t40 or  $\Delta$ t30 output (see your installer or system designer or download from [www.stelrad.com](http://www.stelrad.com)).

For EN442 data, technical and installation information please visit our website: [www.stelrad.com](http://www.stelrad.com) and search product downloads.

Piping connections are the same as the Stelrad Compact.

## WALL MOUNTING INFORMATION

All dimensions in mm. Inches in brackets.




## BRACKET POSITION

A = Closest to wall    B = Furthest from wall    (R) = Recommended mounting position


## MOUNTING BRACKETS

All dimensions in mm. Inches in brackets.




Dimensions	mm	inches	mm	inches	mm	inches	mm	inches
Height	300	11.81	450	17.72	600	23.62	700	27.56
A	65	2.56	65	2.56	65	2.56	65	2.56
B	119	4.69	99	3.90	99	3.90	99	3.90
C	-	-	269	10.59	419	16.50	519	20.43
D	153	6.02	303	11.93	453	17.83	553	21.77
E	185	7.28	335	13.19	485	19.09	585	23.03

**K1 AND K2 LUG POSITIONS** (New as of June 2016).  
All dimensions in mm. Inches in brackets.



L400-1600



L1800-2000

**K1**

Dimensions	mm	in
A 400mm	117	4.61
A 500 - 1100mm	150	5.91
C All	60	2.36

**PANEL HEIGHT**

B		B	
mm	in	mm	in
300	11.81	155	6.10
400	15.75	255	10.04
500	19.69	355	13.98
600	23.62	455	17.93
700	27.56	555	21.85


**K2**

Dimensions	mm	in
A 400 - 1100mm	133	5.24
A 1200 - 2000mm	133	5.24
C All	60	2.36

**CONNECTIONS**

Each radiator comes with ½" inlet connections as standard.


**PIPING OPTIONS**



**EN 442 CERTIFICATION DATA - CETIAT TESTED IN ACCORDANCE WITH BS EN 442**

Type	K1					K2				
	300	400	500	600	700	300	400	500	600	700
Height	300	400	500	600	700	300	400	500	600	700
W/m at 75/65/20	469	629	774	911	1038	929	1177	1411	1634	1848
n-coefficients	1.30	1.29	1.28	1.27	1.27	1.29	1.30	1.31	1.32	1.33
Heated surface area (m <sup>2</sup> /m)	2.09	2.95	3.80	4.66	5.51	3.51	4.92	6.33	7.74	9.15
Weight (kg/m)	11.88	16.13	20.39	24.65	28.91	19.60	26.40	33.20	40.00	46.80
Water contents (l/m)	1.89	2.34	2.80	3.25	3.77	3.70	4.67	5.63	6.60	7.63
Wall to tap centre (mm)	54	54	54	54	54	76	76	76	76	76

## PRESSURE DROPS



Type	Kv
P1 / K1	1.67
P+ / K2	3.32
K3	3.65

A shade for every room, for every interior. Opt for warm elegance, baroque ambience or modern minimalism.

## STANDARD COLOUR

Stelrad Radiators are available in white (RAL 9016) as standard, however the specific radiators identified are now available in a variety of colours.



RAL 9016  
Traffic white

## NATURAL COLOURS



NT110  
Papyrus white




NT120  
Pearl white




NT130  
Champagne




NT140  
Beige



NT160  
Pebble grey



NT170  
Quartz grey



SN150  
Sepia



SN110  
Cream white




SN120  
Cream




SN130  
Mocca



SN140  
Bordeaux



SN160  
Pale blue




SN170  
Black


## METALLIC COLOURS



ML110  
Dove grey




ML120  
Titanium grey




ML140  
Granite



ML150  
Cappuccino




ML160  
Terra brown



ML170  
Graphite black

## RAL COLOURS



A1004  
Golden yellow



A2003  
Pastel orange



A3002  
Carmine red




A3003  
Robin red




A5002  
Ultramarine blue




A6018  
Yellow green



A7001  
Silver grey



A7011  
Iron grey




A7016  
Anthracite grey



A7030  
Stone grey




A7035  
Light grey



A8017  
Chocolate brown



A9003  
Signal white



A9005  
Jet black

\*Please note: When choosing a colour only the front fascia panel can be coloured. Where the product height is 1000mm and 1200mm, the emitter, top grille and side panels are black. If the product height is 1800mm and 2000mm, the emitter, top grille and side panels are white.

FOR FURTHER INFORMATION ON RAL COLOURS PLEASE VISIT [WWW.RALCOLOR.COM](http://WWW.RALCOLOR.COM)

The colours shown are reproduced as accurately as this process will allow and can be made to order on the identified products. All colour radiators have up to an 8 week lead time, and when a coloured radiator or radiators have been ordered they cannot be cancelled or returned. To request a colour chart please email [marketing@stelrad.com](mailto:marketing@stelrad.com)